



RollSeal™

AUTOMATED DOOR SYSTEMS

Exclusive to Global Finishing Solutions® (GFS) paint booths and finishing equipment, RollSeal™ Automated Doors eliminate the space needed for traditional swing or wing-style doors, minimizing the total booth footprint and saving valuable shop space. With their heavy-duty fabric, RollSeal Doors are durable and low maintenance, providing an excellent seal at an affordable price.

Superior Seal & Contamination Control

With a unique, patented design, RollSeal's triple-layered fabric door and airtight seal prevent overspray from escaping the booth and keep contaminants out of your paint jobs. RollSeal Doors operate at the press of a button, and the controller allows you to set the door's speed as it rolls up and down, ensuring smooth starts and stops. With the ability to adjust the door operation speeds, air is not disturbed during operation, keeping dirt and dust out of the booth.



Safety

RollSeal Doors are built in compliance with NFPA, UL/CUL and ETL/ETL-C safety standards. By trapping hazardous overspray and vapors inside the booth, RollSeal Doors create a safer shop environment. Additionally, RollSeal Doors with motorized operators feature an auto-reverse sensor and an emergency manual egress system in case of door or power failure.

Easy Installation

All RollSeal Doors come complete with heavy-duty mounting tracks and a horizontal header with the roll-up door pre-installed. The door system can be installed easily at the entrance or exit of your paint booth. Simply assemble the tracks and header, attach the frame to the booth and mount the controller. RollSeal Doors require less structural support than metal roll-up doors and have minimal failure points to decrease maintenance.

Flexible, High-Quality Construction

RollSeal's triple-layered fabric with air between layers helps to maintain the desired heat levels inside the booth, meeting cure temperature requirements. With fewer moving parts than traditional roll-up doors, less time and money is spent replacing rollers, tracks, panels and hinges. RollSeal's fabric doors are impact resistant; however, if they are punctured or damaged, they can be easily repaired or replaced at a fraction of the cost of a metal roll-up door.

Customized Solutions

RollSeal can custom design a door using your parameters and drawings, providing a solution for openings up to 24 feet wide and 24 feet high. In addition to product entrance and exit, RollSeal Automated Door Systems can be used in sideload booth systems to control contamination and airflow between bays.

All designs, specifications and components are subject to change at the manufacturer's sole discretion at any time without notice.

